

1. Identification

Product identifier	REDKEN SMOOTHING SPRAY
Other means of identification	
SDS number	21-91-0000177
Recommended use	Personal care product used for cosmetic effect.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	

US Address: L'Oreal USA Products, Inc
133 Terminal Avenue
Clark, NJ 07066
USA

Canadian Address: L'Oreal Canada
4895 rue Hickmore
Ville St-Laurent, H4T 1K5
Canada

Emergency Phone # : 1-800-535-5053 (International: 352-323-3500)
In Canada - 1-613-996-6666 (Canutec (*666 Cellular))

For further Information: 1-732-499-2741

Poison Control # : 412-390-3326

2. Hazard(s) identification

Physical hazards	Flammable aerosols Gases under pressure	Category 1 Liquefied gas
Health hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response

Wash hands after handling.

Storage

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
HYDROFLUOROCARBON 152A		75-37-6	30
ETHANOL		64-17-5	5.6

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Not available.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
ETHANOL (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
HYDROFLUOROCARBON 152A (CAS 75-37-6)	TWA	2700 mg/m3 1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Applicable for industrial settings only. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing.

Respiratory protection Applicable for industrial settings only. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Aerosol.

Color Not available.

Odor Characteristic.

Odor threshold Not available.

pH 8.2 - 9.2 (liquid)

Melting point/freezing point Not available.

Initial boiling point and boiling range > 212 °F (> 100 °C) (liquid)

Flash point 118.4 °F (48.0 °C) Closed Cup (liquid)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Fire point < 212.00 °F (< 100.00 °C) ISO 2592

Heat of combustion (NFPA 30B) 7 kJ/g

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	No adverse effects due to eye contact are expected.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics
Not available.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
REDKEN SMOOTHING SPRAY		

Acute

Oral

ATEmix 877200 mg/kg

Components	Species	Test Results
------------	---------	--------------

ETHANOL (CAS 64-17-5)

Acute

Dermal

LD50 Rabbit > 20000 mg/kg

Inhalation

Vapor

LC50 Rat 124.7 mg/l, 4 h OECD 403

Oral

LD50 Rat 10470 mg/kg OECD 401

HYDROFLUOROCARBON 152A (CAS 75-37-6)

Acute

Inhalation

Gas

LC50 Rat > 437500 ppm, 4 h

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. No adverse effects due to skin contact are expected.

Irritation Corrosion - Skin

ETHANOL

OECD 404

Result: Not Irritating

Species: Rabbit

HYDROFLUOROCARBON 152A

Result: Contact with liquid form may cause frostbite.

Serious eye damage/eye irritation Due to partial or complete lack of data the classification is not possible. No adverse effects due to eye contact are expected.

Irritation Corrosion - Eye

ETHANOL

OECD 405

Result: Irritating

Species: Rabbit

HYDROFLUOROCARBON 152A

Result: Contact with liquid form may cause frostbite.

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization

ETHANOL

OECD 406

Result: Not Sensitizing

Species: Guinea pig

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Mutagenicity
ETHANOL

Result: In vitro and in vivo tests did not show mutagenic effects.

HYDROFLUOROCARBON 152A

Result: In vitro and in vivo tests did not show mutagenic effects.

Carcinogenicity

Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

Possible reproductive hazard.

Developmental effects

ETHANOL

> 20000 ppm OECD 414, No effects on development

Result: NOAEL

Species: Rat

HYDROFLUOROCARBON 152A

50000 ppm OECD 414

Result: NOAEC

Species: Rat

Reproductivity

ETHANOL

20700 mg/kg bw/d OECD 416, No effects on fertility

Result: NOAEL

Species: Rat

HYDROFLUOROCARBON 152A

25000 ppm

Result: NOAEL

Species: Rat

Specific target organ toxicity - single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure

Due to partial or complete lack of data the classification is not possible.

ETHANOL

1730 mg/kg bw/d OECD 408, Oral

Result: NOAEL

Species: Rat

HYDROFLUOROCARBON 152A

25000 ppm OECD 453, Inhalation

Result: NOAEC

Species: Rat

Test Duration: 104 wk

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Further information

The reference to any animal testing for individual constituents mentioned in this document is based on public, third-party data.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
ETHANOL (CAS 64-17-5)			
Aquatic			
Acute			
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h
Chronic			
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212

Components	Species		Test Results
HYDROFLUOROCARBON 152A (CAS 75-37-6)			
Aquatic			
Acute			
Algae	EC50	Algae	47.755 mg/l QSAR
Crustacea	EC50	Daphnia	146.695 mg/l QSAR
Fish	LC50	Fish	295.783 mg/l QSAR
Persistence and degradability			
Biodegradability			
Percent degradation (Aerobic biodegradation)			
ETHANOL		84 %	Result: Readily Biodegradable
			Test Duration: 20 d
Bioaccumulative potential			
Partition coefficient n-octanol / water (log Kow)			
ETHANOL		-0.31	
HYDROFLUOROCARBON 152A		0.75	
Mobility in soil		No data available.	
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal considerations			
Disposal instructions		Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations		Dispose in accordance with all applicable regulations.	
Hazardous waste code		This product is ignitable (D001) RCRA hazardous wastes when intended for disposal.	
Waste from residues / unused products		Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging		Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.	
14. Transport information			
DOT			
FINISHED GOODS			
UN number	UN1950		
UN proper shipping name	AEROSOLS, FLAMMABLE, Limited Quantity		
Class	2.1		
Packing group	Not applicable.		
Transport hazard class(es)			
Label(s)	Limited Quantity		
Packaging exceptions	306		
LTD QTY Net Inner Capacity	1.0 L		
BULK			
UN number	UN1170		
UN proper shipping name	ETHANOL SOLUTION		
Class	3		
Packing group	III		
Transport hazard class(es)			
Label(s)	3		
Special provisions	24, B1, IB3, T2, TP1		
Packaging non bulk	203		
IATA			
FINISHED GOODS			
UN number	ID8000		
UN proper shipping name	CONSUMER COMMODITY		

Class	9 - Class 9
Packing group	Not applicable.
ERG Number	9L
BULK	
UN number	UN1170
UN proper shipping name	ETHANOL SOLUTION
Class	3
Packing group	III
ERG Number	3L
IMDG	
FINISHED GOODS	
UN number	UN1950
UN proper shipping name	AEROSOLS, FLAMMABLE, Limited Quantity
Class	2.1
Packing group	Not applicable.
Environmental Hazards	
Marine pollutant	No.
Transport hazard class(es)	
Label(s)	Limited Quantity
EmS	F-D, S-U
LTD QTY Net Inner Capacity	1.0 L
BULK	
UN number	UN1170
UN proper shipping name	ETHANOL SOLUTION
Class	3
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
General information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHANOL (CAS 64-17-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No (Exempt)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROFLUOROCARBON 152A (CAS 75-37-6)

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHANOL (CAS 64-17-5)

Low priority

16. Other information, including date of preparation or last revision

Issue date 03-08-2022

Version # 01

NFPA ratings Health: 0
Flammability: 4
Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.