Common Name: FOOD GRADE SILICONE 03040

Manufacturer: CRC

SDS Revision Date: 8/12/2014

SDS Format: GHS-US

Grainger Item Number(s): 3EED7

Manufacturer Model Number(s):

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

1. IDENTIFICATION
2. HAZARD(S) IDENTIFICATION
3. COMPOSITION/INFORMATION ON INGREDIENTS
4. FIRST-AID MEASURES
5. FIRE-FIGHTING MEASURES
6. ACCIDENTAL RELEASE MEASURES
7. HANDLING AND STORAGE
8. EXPOSURE CONTROLS/PERSONAL PROTECTION
9. PHYSICAL AND CHEMICAL PROPERTIES
10. STABILITY AND REACTIVITY
11. TOXICOLOGICAL INFORMATION
12. ECOLOGICAL INFORMATION
13. DISPOSAL CONSIDERATIONS
14. TRANSPORT INFORMATION
15. REGULATORY INFORMATION
16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION

CRC(R*)

SAFETY DATA SHEET

1. IDENTIFICATION

PRODUCT IDENTIFIER: FOOD GRADE SILICONE

OTHER MEANS OF IDENTIFICATION:

PRODUCT CODE: 03040

RECOMMENDED USE: SILICONE-BASED MULTI-PURPOSE LUBRICANT

RECOMMENDED RESTRICTIONS: NONE KNOWN.

MANUFACTURER/IMPORTER/SUPPLIER/DISTRIBUTOR INFORMATION:

MANUFACTURED OR SOLD BY:

COMPANY NAME: CRC INDUSTRIES, INC.

ADDRESS:
885 LOUIS DR.
WARMINSTER, PA 18974
US

TELEPHONE:

GENERAL INFORMATION: 215-674-4300

TECHNICAL ASSISTANCE: 800-521-3168

CUSTOMER SERVICE: 800-272-4620

24-HOUR EMERGENCY (CHEMTREC):
800-424-9300 (US)
703-527-3887 (INTERNATIONAL)

WEBSITE: WWW.CRCINDUSTRIES.COM

2. HAZARD(S) IDENTIFICATION

PHYSICAL HAZARDS:

FLAMMABLE AEROSOLS: CATEGORY 1

GASES UNDER PRESSURE: LIQUEFIED GAS

HEALTH HAZARDS:

REPRODUCTIVE TOXICITY (FERTILITY): CATEGORY 2

SPECIFIC TARGET ORGAN TOXICITY, SINGLE EXPOSURE: CATEGORY 3 NARCOTIC EFFECTS

SPECIFIC TARGET ORGAN TOXICITY, REPEATED EXPOSURE: CATEGORY 2

ASPIRATION HAZARD: CATEGORY 1

ENVIRONMENTAL HAZARDS:

HAZARDOUS TO THE AQUATIC ENVIRONMENT, ACUTE HAZARD: CATEGORY 3

HAZARDOUS TO THE AQUATIC ENVIRONMENT, LONG-TERM HAZARD: CATEGORY 3

OSHA DEFINED HAZARDS: NOT CLASSIFIED.

LABEL ELEMENTS:

FLAME
GAS CYLINDER
HEALTH HAZARD
EXCLAMATION MARK

SIGNAL WORD: DANGER

HAZARD STATEMENT:
EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE DROWSINESS OR DIZZINESS. SUSPECTED OF DAMAGING FERTILITY. MAY CAUSE DAMAGE TO ORGANS (NERVOUS SYSTEM, UPPER RESPIRATORY TRACT, SKIN, EYES) THROUGH PROLONGED OR REPEATED EXPOSURE. HARMFUL TO AQUATIC LIFE. HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT:

PREVENTION:
OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING. DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE. DO NOT APPLY WHILE EQUIPMENT IS ENERGIZED.

PRESSURIZED CONTAINER:
DO NOT PIERCE OR BURN, EVEN AFTER USE. EXTINGUISH ALL FLAMES, PILOT LIGHTS AND HEATERS. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE. USE ONLY WITH ADEQUATE VENTILATION; MAINTAIN VENTILATION DURING USE AND UNTIL ALL VAPORS ARE GONE. OPEN DOORS AND WINDOWS OR USE OTHER MEANS TO ENSURE A FRESH AIR SUPPLY DURING USE AND WHILE PRODUCT IS DRYING. IF YOU EXPERIENCE ANY SYMPTOMS LISTED ON THIS LABEL, INCREASE VENTILATION OR LEAVE THE AREA. DO NOT BREATHE GAS. DO NOT BREATHE MIST OR VAPOR. WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION. AVOID RELEASE TO THE ENVIRONMENT.

RESPONSE:

IF SWALLOWED:
IMMEDIATELY CALL A POISON CENTER/DOCTOR. DO NOT INDUCE VOMITING.

IF INHALED:
REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.

IF EXPOSED OR CONCERNED: GET MEDICAL ATTENTION.

STORAGE:
STORE IN A WELL-VENTILATED PLACE. STORE LOCKED UP. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F. EXPOSURE TO HIGH TEMPERATURE MAY CAUSE CAN TO BURST.

DISPOSAL:
DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL REGULATIONS.

HAZARD(S) NOT OTHERWISE CLASSIFIED (HNOC):
STATIC ACCUMULATING FLAMMABLE LIQUID CAN BECOME ELECTROSTATICALLY CHARGED EVEN IN BONDED AND GROUNDED EQUIPMENT. SPARKS MAY IGNITE LIQUID AND VAPOR.

MAY CAUSE FLASH FIRE OR EXPLOSION.

3. COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES:

CHEMICAL NAME	COMMON NAME AND SYNONYMS	CAS NUMBER	%
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT		64742-49-0	40 - 50
1,1-DIFLUOROETHANE	HFC-152A	75-37-6	30 - 40
2-METHYLPENTANE		107-83-5	10 - 20
POLYDIMETHYLSILOXANE		63148-62-9	3 - 5
N-HEXANE		110-54-3	1 - 3
2,2-DIMETHYLBUTANE		75-83-2	<0.2

SPECIFIC CHEMICAL IDENTITY AND/OR PERCENTAGE OF COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

4. FIRST-AID MEASURES

INHALATION:
REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

SKIN CONTACT:
WASH OFF WITH SOAP AND PLENTY OF WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PERSISTS. TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

EYE CONTACT:
RINSE WITH WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PERSISTS.

INGESTION:
CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD LOW SO THAT STOMACH CONTENT DOESN'T GET INTO THE LUNGS. ASPIRATION MAY CAUSE PULMONARY EDEMA AND PNEUMONITIS.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:
VAPORS HAVE A NARCOTIC EFFECT AND MAY CAUSE HEADACHE, FATIGUE, DIZZINESS AND NAUSEA. MAY CAUSE DROWSINESS OR DIZZINESS. PROLONGED EXPOSURE MAY CAUSE CHRONIC EFFECTS.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
PROVIDE GENERAL SUPPORTIVE MEASURES AND TREAT SYMPTOMATICALLY.

GENERAL INFORMATION:

IF EXPOSED OR CONCERNED:
GET MEDICAL ADVICE/ATTENTION. ENSURE THAT MEDICAL PERSONNEL ARE AWARE OF THE MATERIAL(S) INVOLVED, AND TAKE PRECAUTIONS TO PROTECT THEMSELVES.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:
WATER SPRAY. WATER FOG. FOAM. DRY CHEMICAL POWDER, CARBON DIOXIDE, SAND OR EARTH MAY BE USED FOR SMALL FIRES ONLY.

UNSUITABLE EXTINGUISHING MEDIA:
DO NOT USE WATER JET AS AN EXTINGUISHER, AS THIS WILL SPREAD THE FIRE.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:
CONTENTS UNDER PRESSURE. PRESSURIZED CONTAINER MAY EXPLODE WHEN EXPOSED TO HEAT OR FLAME. THIS PRODUCT IS A POOR CONDUCTOR OF ELECTRICITY AND CAN BECOME ELECTROSTATICALLY CHARGED. IF SUFFICIENT CHARGE IS ACCUMULATED, IGNITION OF FLAMMABLE MIXTURES CAN OCCUR. STATIC ELECTRICITY ACCUMULATION MAY BE SIGNIFICANTLY INCREASED BY THE PRESENCE OF SMALL QUANTITIES OF WATER OR OTHER CONTAMINANTS. MATERIAL WILL FLOAT AND MAY IGNITE ON SURFACE OF WATER.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:
FIREFIGHTERS MUST USE STANDARD PROTECTIVE EQUIPMENT INCLUDING FLAME RETARDANT COAT, HELMET WITH FACE SHIELD, GLOVES, RUBBER BOOTS, AND IN ENCLOSED SPACES, SCBA.

FIRE-FIGHTING EQUIPMENT/INSTRUCTIONS:

IN CASE OF FIRE:
STOP LEAK IF SAFE TO DO SO. MOVE CONTAINERS FROM FIRE AREA IF YOU CAN DO SO WITHOUT RISK. CONTAINERS SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD UP. IN THE EVENT OF FIRE, COOL TANKS WITH WATER SPRAY.

GENERAL FIRE HAZARDS: EXTREMELY FLAMMABLE AEROSOL.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
KEEP UNNECESSARY PERSONNEL AWAY. KEEP PEOPLE AWAY FROM AND UPWIND OF SPILL/LEAK. KEEP OUT OF LOW AREAS. REMOVE ALL POSSIBLE SOURCES OF IGNITION IN THE SURROUNDING AREA. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. DO NOT BREATHE GAS. DO NOT BREATHE MIST OR VAPOR. DO NOT TOUCH DAMAGED CONTAINERS OR SPILLED MATERIAL UNLESS WEARING APPROPRIATE PROTECTIVE CLOTHING. VENTILATE CLOSED SPACES BEFORE ENTERING THEM. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES CANNOT BE CONTAINED. FOR PERSONAL PROTECTION, SEE SECTION 8 OF THE SDS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

ELIMINATE ALL IGNITION SOURCES (NO SMOKING, FLARES, SPARKS, OR FLAMES IN IMMEDIATE AREA). KEEP COMBUSTIBLES (WOOD, PAPER, OIL, ETC.) AWAY FROM SPILLED MATERIAL. THIS PRODUCT IS MISCIBLE IN WATER. STOP THE FLOW OF MATERIAL, IF THIS IS WITHOUT RISK. COLLECT SPILLAGE. DIKE FAR AHEAD OF SPILL

FOR LATER DISPOSAL. WIPE UP WITH ABSORBENT MATERIAL (E.G. CLOTH, FLEECE). CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION. PREVENT ENTRY INTO WATERWAYS, SEWER, BASEMENTS OR CONFINED AREAS. FOR WASTE DISPOSAL, SEE SECTION 13 OF THE SDS.

ENVIRONMENTAL PRECAUTIONS:
AVOID RELEASE TO THE ENVIRONMENT. CONTACT LOCAL AUTHORITIES IN CASE OF SPILLAGE TO DRAIN/AQUATIC ENVIRONMENT. PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT CONTAMINATE WATER. AVOID DISCHARGE INTO DRAINS, WATER COURSES OR ONTO THE GROUND. USE APPROPRIATE CONTAINMENT TO AVOID ENVIRONMENTAL CONTAMINATION.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:
OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. MINIMIZE FIRE RISKS FROM FLAMMABLE AND COMBUSTIBLE MATERIALS (INCLUDING COMBUSTIBLE DUST AND STATIC ACCUMULATING LIQUIDS) OR DANGEROUS REACTIONS WITH INCOMPATIBLE MATERIALS. HANDLING OPERATIONS THAT CAN PROMOTE ACCUMULATION OF STATIC CHARGES INCLUDE BUT ARE NOT LIMITED TO:
MIXING, FILTERING, PUMPING AT HIGH FLOW RATES, SPLASH FILLING, CREATING MISTS OR SPRAYS, TANK AND CONTAINER FILLING, TANK CLEANING, SAMPLING, GAUGING, SWITCH LOADING, VACUUM TRUCK OPERATIONS.

PRESSURIZED CONTAINER:
DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT USE IF SPRAY BUTTON IS MISSING OR DEFECTIVE. DO NOT SPRAY ON A NAKED FLAME OR ANY OTHER INCANDESCENT MATERIAL. DO NOT SMOKE WHILE USING OR UNTIL SPRAYED SURFACE IS THOROUGHLY DRY. DO NOT CUT, WELD, SOLDER, DRILL, GRIND, OR EXPOSE CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. USE CAUTION AROUND ENERGIZED EQUIPMENT. THE METAL CONTAINER WILL CONDUCT ELECTRICITY IF IT CONTACTS A LIVE SOURCE. THIS MAY RESULT IN INJURY TO THE USER FROM ELECTRICAL SHOCK AND/OR FLASH FIRE. DO NOT BREATHE MIST OR VAPOR. DO NOT BREATHE GAS. AVOID CONTACT DURING PREGNANCY/WHILE NURSING. AVOID PROLONGED EXPOSURE. USE ONLY IN WELL-VENTILATED AREAS. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING, DO NOT EAT, DRINK OR SMOKE. WASH HANDS THOROUGHLY AFTER HANDLING. OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES. AVOID RELEASE TO THE ENVIRONMENT. DO NOT EMPTY INTO DRAINS. FOR PRODUCT USAGE INSTRUCTIONS, PLEASE SEE THE PRODUCT LABEL.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
LEVEL 3 AEROSOL.

PRESSURIZED CONTAINER. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F. DO NOT PUNCTURE, INCINERATE OR CRUSH. DO NOT HANDLE OR STORE NEAR AN OPEN FLAME, HEAT OR OTHER SOURCES OF IGNITION. THIS MATERIAL CAN ACCUMULATE STATIC CHARGE WHICH MAY CAUSE SPARK AND BECOME AN IGNITION SOURCE. AVOID SPARK PROMOTERS. THESE ALONE MAY BE

INSUFFICIENT TO REMOVE STATIC ELECTRICITY. STORE IN A WELL-VENTILATED PLACE.

STORE AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10 OF THE SDS). KEEP OUT OF THE REACH OF CHILDREN.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS:

US. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINANTS (29 CFR 1910.1000):

COMPONENTS	TYPE	VALUE
N-HEXANE (CAS 110-54-3)	PEL	1800 MG/M3 500 PPM

US. ACGIH THRESHOLD LIMIT VALUES:

COMPONENTS	TYPE	VALUE
2,2-DIMETHYLBUTANE (CAS 75-83-2)	STEL	1000 PPM
	TWA	500 PPM
2-METHYLPENTANE (CAS 107-83-5)	STEL	1000 PPM
	TWA	500 PPM
N-HEXANE (CAS 110-54-3)	TWA	50 PPM

US. NIOSH:

POCKET GUIDE TO CHEMICAL HAZARDS:

COMPONENTS	TYPE	VALUE
2,2-DIMETHYLBUTANE (CAS 75-83-2)	CEILING	1800 MG/M3 510 PPM
	TWA	350 MG/M3 100 PPM
2-METHYLPENTANE (CAS 107-83-5)	CEILING	1800 MG/M3 510 PPM
	TWA	350 MG/M3 100 PPM
N-HEXANE (CAS 110-54-3)	TWA	180 MG/M3 50 PPM

US. AIHA WORKPLACE ENVIRONMENTAL EXPOSURE LEVEL (WEEL) GUIDES:

COMPONENTS	TYPE	VALUE

1,1-DIFLUOROETHANE (CAS 75-37-6)	TWA	2700 MG/M3 1000 PPM

BIOLOGICAL LIMIT VALUES:

ACGIH BIOLOGICAL EXPOSURE INDICES:

COMPONENTS	VALUE	DETERMINANT	SPECIMEN	SAMPLING TIME
N-HEXANE (CAS 110-54-3)	0.4 MG/L	2,5-HEXANEDION, WITHOUT HYDROLYSIS	URINE	*

* - FOR SAMPLING DETAILS, PLEASE SEE THE SOURCE DOCUMENT.

EXPOSURE GUIDELINES:

US - CALIFORNIA OELS:

SKIN DESIGNATION:

N-HEXANE (CAS 110-54-3) CAN BE ABSORBED THROUGH THE SKIN.

US ACGIH THRESHOLD LIMIT VALUES:

SKIN DESIGNATION:

N-HEXANE (CAS 110-54-3) CAN BE ABSORBED THROUGH THE SKIN.

APPROPRIATE ENGINEERING CONTROLS:
GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS. IF APPLICABLE, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. IF EXPOSURE LIMITS HAVE NOT BEEN ESTABLISHED, MAINTAIN AIRBORNE LEVELS TO AN ACCEPTABLE LEVEL.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES).

SKIN PROTECTION:

HAND PROTECTION:

WEAR PROTECTIVE GLOVES SUCH AS: NITRILE. POLYVINYL CHLORIDE (PVC).VITON(R*).

OTHER: WEAR APPROPRIATE CHEMICAL RESISTANT CLOTHING.

RESPIRATORY PROTECTION:
IF ENGINEERING CONTROLS ARE NOT FEASIBLE OR IF EXPOSURE EXCEEDS THE APPLICABLE EXPOSURE LIMITS, USE A NIOSH-APPROVED CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE. USE A SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES AND FOR EMERGENCIES. AIR MONITORING IS NEEDED TO DETERMINE ACTUAL EMPLOYEE EXPOSURE LEVELS.

THERMAL HAZARDS: WEAR APPROPRIATE THERMAL PROTECTIVE CLOTHING, WHEN NECESSARY.

GENERAL HYGIENE CONSIDERATIONS:
WHEN USING, DO NOT EAT, DRINK OR SMOKE. ALWAYS OBSERVE GOOD PERSONAL HYGIENE MEASURES, SUCH AS WASHING AFTER HANDLING THE MATERIAL AND BEFORE EATING, DRINKING, AND/OR SMOKING. ROUTINELY WASH WORK CLOTHING AND PROTECTIVE EQUIPMENT TO REMOVE CONTAMINANTS.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

PHYSICAL STATE: LIQUID.

FORM: AEROSOL.

COLOR: CLEAR WATER-WHITE.

ODOR: MILD SOLVENT.

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT AVAILABLE.

MELTING POINT/FREEZING POINT: NOT AVAILABLE.

INITIAL BOILING POINT AND BOILING RANGE: 118.4 DEG. F (48 DEG. C) ESTIMATED

FLASH POINT: <0 DEG. F (<-17.8 DEG. C) TAG CLOSED CUP

EVAPORATION RATE: FAST.

FLAMMABILITY (SOLID, GAS): NOT AVAILABLE.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

FLAMMABILITY LIMIT - LOWER (%): 1 % ESTIMATED
FLAMMABILITY LIMIT - UPPER (%): 8 % ESTIMATED

VAPOR PRESSURE: 3083.3 HPA ESTIMATED

VAPOR DENSITY: >1 (AIR = 1)

RELATIVE DENSITY: 0.81 ESTIMATED

SOLUBILITY (WATER): NEGLIGIBLE.

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE.

AUTO-IGNITION TEMPERATURE: 489.2 DEG. F (254 DEG. C) ESTIMATED

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

VISCOSITY (KINEMATIC): NOT AVAILABLE.

PERCENT VOLATILE: 97 % ESTIMATED

10. STABILITY AND REACTIVITY

REACTIVITY:
THE PRODUCT IS STABLE AND NON-REACTIVE UNDER NORMAL CONDITIONS OF USE, STORAGE AND TRANSPORT.

CHEMICAL STABILITY: MATERIAL IS STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS:
NO DANGEROUS REACTION KNOWN UNDER CONDITIONS OF NORMAL USE.

CONDITIONS TO AVOID:
HEAT, FLAMES AND SPARKS. CONTACT WITH INCOMPATIBLE MATERIALS.

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS. CHLORINE.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES.

11. TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE:

INGESTION: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

INHALATION:
VAPORS HAVE A NARCOTIC EFFECT AND MAY CAUSE HEADACHE, FATIGUE, DIZZINESS AND NAUSEA. PROLONGED INHALATION MAY BE HARMFUL. MAY CAUSE DAMAGE TO ORGANS BY INHALATION.

SKIN CONTACT:
PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY IRRITATION. FREQUENT OR PROLONGED CONTACT MAY DEFAT AND DRY THE SKIN, LEADING TO DISCOMFORT AND DERMATITIS.

EYE CONTACT: DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS: SYMPTOMS OF OVEREXPOSURE MAY BE HEADACHE, DIZZINESS, TIREDNESS, NAUSEA AND VOMITING.

INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. NARCOTIC EFFECTS.

PRODUCT	SPECIES	TEST RESULTS

FOOD GRADE SILICONE:

ACUTE:

DERMAL:

LD50	RABBIT	3767.2212 MG/KG ESTIMATED

INHALATION:

LC50	RAT	62.4636 MG/L, 4 HOURS ESTIMATED

ORAL:

LD50	RAT	23868.4531 MG/KG ESTIMATED

* ESTIMATES FOR PRODUCT MAY BE BASED ON ADDITIONAL COMPONENT DATA NOT SHOWN.

SKIN CORROSION/IRRITATION:
PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY IRRITATION.

SERIOUS EYE DAMAGE/EYE IRRITATION:
DIRECT CONTACT WITH EYES MAY CAUSE TEMPORARY IRRITATION.

RESPIRATORY SENSITIZATION: NOT AVAILABLE.

SKIN SENSITIZATION:
THIS PRODUCT IS NOT EXPECTED TO CAUSE SKIN SENSITIZATION.

GERM CELL MUTAGENICITY:
NO DATA AVAILABLE TO INDICATE PRODUCT OR ANY COMPONENTS PRESENT AT GREATER THAN 0.1% ARE MUTAGENIC OR GENOTOXIC.

CARCINOGENICITY:
THIS PRODUCT IS NOT CONSIDERED TO BE A CARCINOGEN BY IARC, ACGIH, NTP, OR OSHA.

REPRODUCTIVE TOXICITY: SUSPECTED OF DAMAGING FERTILITY.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: NARCOTIC EFFECTS.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE:
MAY CAUSE DAMAGE TO ORGANS (NERVOUS SYSTEM, UPPER RESPIRATORY TRACT, SKIN, EYES) THROUGH PROLONGED OR REPEATED EXPOSURE.

ASPIRATION HAZARD: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CHRONIC EFFECTS:

PROLONGED INHALATION MAY BE HARMFUL. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

OVEREXPOSURE TO N-HEXANE MAY CAUSE PROGRESSIVE AND POTENTIALLY IRREVERSIBLE DAMAGE TO THE PERIPHERAL NERVOUS SYSTEM, PARTICULARLY IN THE ARMS AND LEGS.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:
HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS. ACCUMULATION IN AQUATIC ORGANISMS IS EXPECTED.

PRODUCT		SPECIES	TEST RESULTS
FOOD GRADE SILICONE:			
AQUATIC:			
FISH	LC50	FISH	613.7199 MG/L, 96 HOURS ESTIMATED

PRODUCT		SPECIES	TEST RESULTS
N-HEXANE (CAS 110-54-3):			
AQUATIC:			
FISH	LC50	FATHEAD MINNOW (PIMEPHALES PROMELAS)	2.101 - 2.981 MG/L, 96 HOURS
POLYDIMETHYLSILOXANE (CAS 63148-62-9):			
AQUATIC:			
FISH	LC50	CHANNEL CATFISH (ICTALURUS PUNCTATUS)	2.36 - 4.15 MG/L, 96 HOURS

* ESTIMATES FOR PRODUCT MAY BE BASED ON ADDITIONAL COMPONENT DATA NOT SHOWN.

PERSISTENCE AND DEGRADABILITY:
NO DATA IS AVAILABLE ON THE DEGRADABILITY OF THIS PRODUCT.

BIOACCUMULATIVE POTENTIAL: NO DATA AVAILABLE.

PARTITION COEFFICIENT N-OCTANOL / WATER (LOG KOW):

1,1-DIFLUOROETHANE	0.75
2,2-DIMETHYLBUTANE	3.82
2-METHYLPENTANE	3.74
N-HEXANE	3.9

MOBILITY IN SOIL: NO DATA AVAILABLE.

OTHER ADVERSE EFFECTS:
NO OTHER ADVERSE ENVIRONMENTAL EFFECTS (E.G. OZONE DEPLETION, PHOTOCHEMICAL OZONE CREATION POTENTIAL, ENDOCRINE DISRUPTION, GLOBAL WARMING POTENTIAL) ARE EXPECTED FROM THIS COMPONENT.

13. DISPOSAL CONSIDERATIONS

DISPOSAL OF WASTE FROM RESIDUES / UNUSED PRODUCTS:
THIS MATERIAL AND ITS CONTAINER MUST BE DISPOSED OF AS HAZARDOUS WASTE. IF DISCARDED, THIS PRODUCT IS CONSIDERED A RCRA IGNITABLE WASTE, D001. CONSULT AUTHORITIES BEFORE DISPOSAL. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE OR CRUSH. DO NOT ALLOW THIS MATERIAL TO DRAIN INTO SEWERS/WATER SUPPLIES. DO NOT CONTAMINATE PONDS, WATERWAYS OR DITCHES WITH CHEMICAL OR USED CONTAINER. DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

HAZARDOUS WASTE CODE:

D001: WASTE FLAMMABLE MATERIAL WITH A FLASH POINT <140 F

CONTAMINATED PACKAGING:
EMPTY CONTAINERS SHOULD BE TAKEN TO AN APPROVED WASTE HANDLING SITE FOR RECYCLING OR DISPOSAL. SINCE EMPTIED CONTAINERS MAY RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

14. TRANSPORT INFORMATION

DOT:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

LABEL(S): 2.1

PACKING GROUP: NOT APPLICABLE.

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

SPECIAL PROVISIONS: N82

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: NONE

PACKAGING BULK: NONE

IATA:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, FLAMMABLE, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.1

SUBSIDIARY RISK:

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS: NO.

ERG CODE: 10L

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: ALLOWED.

CARGO AIRCRAFT ONLY: ALLOWED.

IMDG:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2

SUBSIDIARY RISK:

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS:

MARINE POLLUTANT: NO.

EMS: F-D, S-U

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS:
THIS PRODUCT IS A "HAZARDOUS CHEMICAL" AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

ALL COMPONENTS ARE ON THE U.S. EPA TSCA INVENTORY LIST.

TSCA SECTION 12(B) EXPORT NOTIFICATION (40 CFR 707, SUBPT. D):NOT REGULATED.

SARA 304 EMERGENCY RELEASE NOTIFICATION: NOT REGULATED.

US. OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050):
NOT LISTED.

US EPCRA (SARA TITLE III) SECTION 313 - TOXIC CHEMICAL:

LISTED SUBSTANCE:
N-HEXANE (CAS 110-54-3)

CERCLA HAZARDOUS SUBSTANCE LIST (40 CFR 302.4):
N-HEXANE (CAS 110-54-3)

CERCLA HAZARDOUS SUBSTANCES:

REPORTABLE QUANTITY:

N-HEXANE (CAS 110-54-3) 5000 LBS

SPILLS OR RELEASES RESULTING IN THE LOSS OF ANY INGREDIENT AT OR ABOVE ITS RQ REQUIRE IMMEDIATE NOTIFICATION TO THE NATIONAL RESPONSE CENTER (800-424-8802) AND TO YOUR LOCAL EMERGENCY PLANNING COMMITTEE.

CLEAN AIR ACT (CAA) SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPS) LIST:
N-HEXANE (CAS 110-54-3)

CLEAN AIR ACT (CAA) SECTION 112(R) ACCIDENTAL RELEASE PREVENTION (40 CFR 68.130):
1,1-DIFLUOROETHANE (CAS 75-37-6)

SAFE DRINKING WATER ACT (SDWA): NOT REGULATED.

FOOD AND DRUG ADMINISTRATION (FDA): NOT REGULATED.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):

SECTION 311/312 HAZARD CATEGORIES:
IMMEDIATE HAZARD: YES
DELAYED HAZARD: YES
FIRE HAZARD: YES
PRESSURE HAZARD: YES
REACTIVITY HAZARD: NO

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: NO

US STATE REGULATIONS:

US. CALIFORNIA CONTROLLED SUBSTANCES. CA DEPARTMENT OF JUSTICE (CALIFORNIA HEALTH AND SAFETY CODE SECTION 11100):
NOT LISTED.

US. NEW JERSEY WORKER AND COMMUNITY RIGHT-TO-KNOW ACT:
2,2-DIMETHYLBUTANE (CAS 75-83-2)
2-METHYLPENTANE (CAS 107-83-5)
1,1-DIFLUOROETHANE (CAS 75-37-6)
N-HEXANE (CAS 110-54-3)

US. MASSACHUSETTS RTK - SUBSTANCE LIST:
1,1-DIFLUOROETHANE (CAS 75-37-6)
2-METHYLPENTANE (CAS 107-83-5)
N-HEXANE (CAS 110-54-3)

US. RHODE ISLAND RTK:
1,1-DIFLUOROETHANE (CAS 75-37-6)
N-HEXANE (CAS 110-54-3)

US. PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW LAW:
2,2-DIMETHYLBUTANE (CAS 75-83-2)
2-METHYLPENTANE (CAS 107-83-5)
N-HEXANE (CAS 110-54-3)

US. CALIFORNIA PROPOSITION 65:

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65):

THIS MATERIAL IS NOT KNOWN TO CONTAIN ANY CHEMICALS CURRENTLY LISTED AS CARCINOGENS OR REPRODUCTIVE TOXINS.

VOLATILE ORGANIC COMPOUNDS (VOC) REGULATIONS:

EPA:

VOC CONTENT (40 CFR 51.100(S)): 60 %

CONSUMER PRODUCTS: (40 CFR 59, SUBPT. C): NOT REGULATED

STATE:

CONSUMER PRODUCTS:
THIS PRODUCT IS REGULATED AS A SILICONE BASED MULTI-PURPOSE LUBRICANT. THIS PRODUCT IS COMPLIANT FOR USE IN ALL 50 STATES.

VOC CONTENT (CA): 60 %

VOC CONTENT (OTC): 60 %

INTERNATIONAL INVENTORIES:

COUNTRY(S) OR REGION	INVENTORY NAME	ON INVENTORY (YES/NO)*
AUSTRALIA	AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS)	YES
CANADA	DOMESTIC SUBSTANCES LIST (DSL)	YES
CANADA	NON-DOMESTIC SUBSTANCES LIST (NDSL)	NO
CHINA	INVENTORY OF EXISTING CHEMICAL SUBSTANCES IN CHINA (IECSC)	YES
EUROPE	EUROPEAN INVENTORY OF EXISTING	NO

	COMMERCIAL CHEMICAL SUBSTANCES (EINECS)	
EUROPE	EUROPEAN LIST OF NOTIFIED CHEMICAL SUBSTANCES (ELINCS)	NO
JAPAN	INVENTORY OF EXISTING AND NEW CHEMICAL SUBSTANCES (ENCS)	NO
KOREA	EXISTING CHEMICALS LIST (ECL)	YES
NEW ZEALAND	NEW ZEALAND INVENTORY	YES
PHILIPPINES	PHILIPPINE INVENTORY OF CHEMICALS AND CHEMICAL SUBSTANCES (PICCS)	YES
UNITED STATES & PUERTO RICO	TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY	YES

*A "YES" INDICATES THAT ALL COMPONENTS OF THIS PRODUCT COMPLY WITH THE INVENTORY REQUIREMENTS ADMINISTERED BY THE GOVERNING COUNTRY(S)

A "NO" INDICATES THAT ONE OR MORE COMPONENTS OF THE PRODUCT ARE NOT LISTED OR EXEMPT FROM LISTING ON THE INVENTORY ADMINISTERED BY THE GOVERNING COUNTRY(S).

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION

OR LAST REVISION

ISSUE DATE: 02-03-2014

REVISION DATE: 08-12-2014

PREPARED BY: ALLISON CHO

VERSION #: 02

FURTHER INFORMATION: CRC # 519E-F

HMIS(R*) RATINGS:
HEALTH 2*
FLAMMABILITY 4
PHYSICAL HAZARD 0
PERSONAL PROTECTION B

NFPA RATINGS:
HEALTH 2
FLAMMABILITY 4
INSTABILITY 0

DISCLAIMER:
THE INFORMATION CONTAINED IN THIS DOCUMENT APPLIES TO THIS SPECIFIC MATERIAL AS SUPPLIED. IT MAY NOT BE VALID FOR THIS MATERIAL IF IT IS USED IN

COMBINATION WITH ANY OTHER MATERIALS. THIS INFORMATION IS ACCURATE TO THE BEST OF CRC INDUSTRIES' KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY CRC TO BE ACCURATE. BEFORE USING ANY PRODUCT, READ ALL WARNINGS AND DIRECTIONS ON THE LABEL. FOR FURTHER CLARIFICATION OF ANY INFORMATION CONTAINED ON THIS (M)SDS CONSULT YOUR SUPERVISOR, A HEALTH & SAFETY PROFESSIONAL, OR CRC INDUSTRIES.

MATERIAL NAME: FOOD GRADE SILICONE

SDS: US