MATERIAL SAFETY DATA SHEET

Marianna Industries, Inc. 11222 "I" Street Omaha, Nebraska 68137-1296

Non-Emergency (402) 593-0211 EMERGENCY: Infotrac (800) 457-4280

Revised: 04/07 PRODUCT INFORMATION Page 1 PRODUCT NAME: Marianna[™] Pure Acetone Polish Remover CHEMICAL NAME: ACETONE CHEMICAL TYPE: ___X_ Pure Mixture CAS NUMBER: N/A CHEMICAL STATE: Liquid **INGREDIENTS:** OSHA Z1 OSHA Z1A OSHA Z1A ACGIH ACGIH **PEL TWA** STEL **TWA STEL** 1000 ppm 500 ppm 750 ppm 1000 ppm 750 ppm CAS No. % by Weight/Weight Chemical Name 100.00% 67-64-1 Acetone II B. HAZARDOUS IDENTIFICATION: Haard Category: ___X__ Fire ____ Pressure Reactive X Acute ___X__ Chronic Hazardous Identification Information: Harmful: May cause lung damage if swallowed. Vapors may cause drowsiness and dizziness. Irritating to eyes. Safety Hazards: Extremely Flammable. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing flashback fire danger. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. HAZARDOUS COMPONENTS III B. **NAME** CAS NO. Concentration ACETONE 100.00% 67-64-1 CHEMICAL NAME **Toxicity Data** (ACETONE) LD 50 LC 50

III B. Continued Page 2

IV. FIRST AID MEASURES:

EYE CONTACT: Irritating to eyes. Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.

SKIN CONTACT: Repeated exposure may cause skin dryness or cracking. Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. Call a physician if irritation persists.

INHALATION: Vapors may cause drowsiness and dizziness. Slightly irritating to respiratory system. Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to nearest medical facility.

INGESTION: HARMFUL: May cause lung damaged if swallowed. Do Not Delay. Do not induce vomiting. If victim is alert, rinse mouth and drink ½ to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person. Transport to the nearest medical facility for additional treatment. If vomiting occurs spontaneously, deep head below hips to prevent aspiration.

V . EXPOSURE CONTROL MEASURES:

EYE PROTECTION: Wear safety glasses or full face shield if splashes are likely to occur.

SKIN PROTECTION: Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant. Gloves should be chemical resistant.

OTHER PROTECTIVE EQUIPMENT: Eyewash station and Safety Shower.

RESPIRATORY PROTECTION: Where air-filtering respirators are unsuitable use appropriate positive pressure breathing apparatus.

VI B: FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT: -18 C / 0 F (IP 170)

Explosion / Flammability: ca. 2.1 -13% (V)

Auto Ignition Temperature: 540 C / 1,004 F (ASTM D - 2155)

EXTINGUISHING MEDIA for ACETONE: Alcohol –resistant foam, water spray or fog. Dry Chemical Powder, Carbon Dioxide, Sand or Earth may be used for small fires only.

VII: Physical and Chemical Properties:

Page 3

Boiling Point: -95 C / -139 F Flashpoint: 018 C / 0 F (IP 170)

Melting Point: N/A Vapor Pressure: 24.7 kzps @ 20 C / 68 F

Sol. IN WATER: @ 20 C / 68 F Completely Miscible.

pH: N/A Specific Gravity: 0.788-.0792@22°C

Vapor Density: 2 @ 20 C / 68 F

Evaporation Rate: 5.6 ASTM D 3539, nBuAc=1)

Appearance / Odor of Finished Product: Clear liquid with a sweet slight aromatic bitter odor

STABILITY AND REACTIVITY DATA for ACETONE:

STABILITY: Stable under normal conditions.

INCOMPATABILITY: Strong Oxidizing Agents

DECOMPOSITION: None expected under normal conditions.

IX. ENVIRONMENTAL & DISPOSAL INFORMATION for ACETONE:

ACTION TO TAKE FOR MATERIAL DISPOSAL: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

ACTION TAKEN FIR CONTAINER DISPOSAL: Drain container thoroughly. After draining, vent in a safe place away from fire and sparks. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer

X . PRECAUTIONS FOR SAFE HANDLING, STORAGE AND USE:

Avoid breathing of or contact with material. Only use in a well ventilated area. Wash thoroughly after handling.

Storage: Keep away from flammables, oxidizing agents, and corrosives. Vapor is heavier than air. Beware of accumulation in pits and confined spaces.

Product Transfer: Ensure electrical continuity by bonding and grounding all equipment.

XI. SHIPPING INFORMATION:

Proper Shipping Name: (Acetone)

Hazard Class: 3 (Flammable Liquid)

UN Number: UN 1090

Packing Group: II

Emergency Response Guide # 127

THE SHIPPING CARTON IDENTIFICATION MUST BE LISTED THE SAME AS THE DESCRIPTION ON THE MSDS!!

Mobility: Recover or recycle if possible. Dissolves in water/ Readily biodegradable. Not expected to bio-accumulate significantly.

DISCLAIMER

The information in this MSDS was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond this company's control, it is the users responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising out of the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various government agencies (e.g. DOT, EPA and FDA) may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.