



# MATERIAL SAFETY DATA SHEET

Product Name **STA-LUBE ASSEMBLY LUBE**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier Name** CRC INDUSTRIES (AUST) PTY LIMITED  
**Address** 9 Gladstone Road, Castle Hill, NSW, AUSTRALIA, 2154  
**Telephone** (02) 9634 2088  
**Fax** (02) 9680 4914  
**Emergency** (02) 9634 2088  
**Email** info@crcind.com.au  
**Web Site** http://www.crcind.com.au/  
**Synonym(s)** 3331 - MANUFACTURER'S CODE • 3333 - MANUFACTURER'S CODE • CRC STA-LUBE ASSEMBLY LUBE • MOLY-GRAPH • STA LUBE ASSEMBLY LUBE  
**Use(s)** LUBRICANT  
**SDS Date** 01 Apr 2010

## 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

<b>UN No.</b>	None Allocated	<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>EPG</b>	None Allocated

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	Not Available	64742-52-5	>60%
GRAPHITE	C	7782-42-5	<10%
MOLYBDENUM DISULPHIDE	Mo-S <sub>2</sub>	1317-33-5	<10%

## 4. FIRST AID MEASURES

**Eye** If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**Advice to Doctor** Treat symptomatically

## 5. FIRE FIGHTING MEASURES

<b>Flammability</b>	Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
<b>Fire and Explosion</b>	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing</b>	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
<b>Hazchem Code</b>	None Allocated

## 6. ACCIDENTAL RELEASE MEASURES

<b>Spillage</b>	Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.
-----------------	--

## 7. STORAGE AND HANDLING

<b>Storage</b>	Store in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection systems.
<b>Handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Oil mist, refined mineral	ASCC (AUS)	--	5	--	--
	Graphite (all forms except fibres)	ASCC (AUS)	--	3	--	--
	Insoluble Molybdenum compounds	ASCC (AUS)	--	10	--	--

<b>Biological Limits</b>	No biological limit allocated.
<b>Engineering Controls</b>	Avoid inhalation. Use in well ventilated areas. Maintain vapour levels below the recommended exposure standard.
<b>PPE</b>	Wear splash-proof goggles and rubber or PVC gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. With prolonged use, wear: nitrile or viton (R) gloves.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	DARK OR GREY GREASE	<b>Solubility (Water)</b>	INSOLUBLE
<b>Odour</b>	SLIGHT ODOUR	<b>Specific Gravity</b>	0.9 - 1.0
<b>pH</b>	NOT AVAILABLE	<b>% Volatiles</b>	NOT AVAILABLE
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	COMBUSTIBLE
<b>Vapour Density</b>	> 1 (Air = 1)	<b>Flash Point</b>	> 200°C
<b>Boiling Point</b>	NOT AVAILABLE	<b>Upper Explosion Limit</b>	NOT AVAILABLE
<b>Melting Point</b>	> 320°C	<b>Lower Explosion Limit</b>	NOT AVAILABLE
<b>Evaporation Rate</b>	NOT AVAILABLE		

---

## 10. STABILITY AND REACTIVITY

---

<b>Chemical Stability</b>	Stable under recommended conditions of storage.
<b>Conditions to Avoid</b>	Avoid heat, sparks, open flames and other ignition sources.
<b>Material to Avoid</b>	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
<b>Decomposition</b>	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
<b>Hazardous Reactions</b>	Polymerization is not expected to occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

<b>Health Hazard Summary</b>	Low toxicity. Use safe work practices to avoid eye or skin contact and inhalation. The mineral oil contained within this product is highly refined and therefore is not classifiable as to its carcinogenicity in humans (IARC Group 3).
<b>Eye</b>	Low to moderate irritant. Contact may result in irritation, lacrimation, pain and redness.
<b>Inhalation</b>	Low irritant. Due to product form / nature of use, an inhalation hazard is not anticipated with normal use. However, if product is heated or mists generated, exposure may result in respiratory irritation, headache and nausea.
<b>Skin</b>	Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.
<b>Ingestion</b>	Low toxicity. Ingestion of large quantities may result in nausea, vomiting, abdominal pain, diarrhoea, and drowsiness. Aspiration may result in chemical pneumonitis and pulmonary oedema.
<b>Toxicity Data</b>	No LD50 data available for this product.

---

## 12. ECOLOGICAL INFORMATION

---

<b>Environment</b>	Mineral oils biodegrade slowly and should not be released to waterways or soil. They can float on water, restricting oxygen exchange with possible asphyxiation of aquatic life.
--------------------	--

---

## 13. DISPOSAL CONSIDERATIONS

---

<b>Waste Disposal</b>	For large volumes, mix with flammable solvent and incinerate at approved facility. May be recycled. Avoid contamination of drains or waterways. Contact the manufacturer for additional information.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

---

## 14. TRANSPORT INFORMATION

---

### NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

<b>Shipping Name</b>	None Allocated				
<b>UN No.</b>	None Allocated	<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>EPG</b>	None Allocated

---

## 15. REGULATORY INFORMATION

---

<b>Poison Schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
<b>AICS</b>	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

---

## 16. OTHER INFORMATION

---

<b>Additional Information</b>	MINERAL OILS - SOLVENT REFINED: Animal experiments and human experience have not shown cancer risks when handling solvent refined mineral oils, unlike non refined mineral oils. CLEANING MINERAL OIL CONTAMINATED CLOTHING: Cleaners are advised that when cleaning oil contaminated clothing it is essential that freshly distilled solvent is used for each batch, including final rinse, as even filtered solvent will leave oil residues.
-------------------------------	--

MINERAL OILS - INJECTION: Where high pressure applications are used the risk of accidental injection under the skin exists and may result in an extremely painful and serious injury requiring immediate medical attention. Depending on the pressure used, mineral oils may be injected a considerable distance below the skin and may cause permanent tissue damage. SEEK IMMEDIATE MEDICAL ATTENTION. EXERCISE EXTREME CARE WHEN USING HIGH PRESSURE EQUIPMENT.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air

**Product Name**     **STA-LUBE ASSEMBLY LUBE**

powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**ABBREVIATIONS:**

- ADB - Air-Dry Basis.
- BEI - Biological Exposure Indice(s)
- CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.
- CNS - Central Nervous System.
- EINECS - European INventory of Existing Commercial chemical Substances.
- IARC - International Agency for Research on Cancer.
- M - moles per litre, a unit of concentration.
- mg/m3 - Milligrams per cubic metre.
- NOS - Not Otherwise Specified.
- NTP - National Toxicology Program.
- OSHA - Occupational Safety and Health Administration.
- pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
- ppm - Parts Per Million.
- RTECS - Registry of Toxic Effects of Chemical Substances.
- TWA/ES - Time Weighted Average or Exposure Standard.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared By**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: info@rmt.com.au  
Web: www.rmt.com.au

**SDS Date:**01 Apr 2010

**End of Report**