



DELTA CREATIVE, INC.

Material Safety Data Sheet

2-19-2018: Reivewed file,
more current MSDS/SDS not
available .IMC.

IDENTITY (As Used on label and List) SOBO PREMIUM CRAFT & FABRIC GLUE		Date Prepared September 24, 2010			
SECTION I					
Manufacturer's Name Delta Creative, Inc.		Emergency Telephone Number (800) 423-4135			
Address 2690 Pellissier Place		Telephone Number for Information (562) 695-7969			
City Of Industry, California 90601-1507		Revision September 24, 2010			
SECTION II - Hazardous Ingredients/Identify Information					
Hazardous Components (Specific Chemical Identity; Common Name(s))		OSHA PEL	ACGIH TLV	CA Prop 65	% (optional)
PolyVinyl Acetate Copolymer Emulsion, CAS# 9003-20-7 appx weight = 48%		N/A	N/A	N/A	N/A
Propylene Glycol, CAS# 57-55-6, appx weight < 5%		N/A	N/A	N/A	N/A
Water, apprx weight = 47%		N/A	N/A	N/A	N/A
Chemical Family: Polyvinyl acetate copolymer emulsion adhesive		N/A	N/A	N/A	N/A
Chemical Formula This product contains a non-hazardous mixture of a modified PolyVinyl Acetate Copolymer Emulsion		N/A	N/A	N/A	N/A
DOT Information: Not Regulated, Non Hazardous		N/A	N/A	N/A	N/A
Note: No known chemical compounds listed as carcinogens under OSHA, ACGIH, NTP, IARC, California Prop 65, or Other.		N/A	N/A	N/A	N/A
SECTION III -Physical/Chemical Characteristics					
Boiling Point		Specific Gravity (H ₂ O = 1)		1.1 - 1.2	
>212°F/100°C					
Vapor Pressure (mm Hg.)		Melting Point		N/A	
N/A					
Vapor Density (AIR = 1)		Evaporation Rate (Butyl Acetate = 1)		<1	
>1					
Solubility in Water Dilutable					
Appearance and Odor White liquid with a low acrylic odor. Clear Rubbery When Dry					
SECTION IV -Fire and Explosion Hazard Data					
Flash Point (Method Used) Not combustible.		Flammable Limits Not Flammable		LEL N/A	
				UEL N/A	
Extinguishing Media Dry chemical, CO ₂ , water fog					
Special Fire Fighting Procedures For precaution use self contained breathing apparatus.					
Unusual Fire and Explosion Hazards Product will not burn but may spatter if temperature exceeds boiling point. Plastic bottle may burn and give off oxides of Carbon/Nitrogen.					

SOBO PREMIUM CRAFT FABRIC GLUE

SECTION V -Reactivity Data				
Stability	Unstable		Conditions to Avoid None known	
	Stable	X		
Incompatibility (<i>Materials to Avoid</i>)				
Strong acids and alkalis.				
Hazardous Decomposition or Byproducts				
None known				
Hazardous Polymerization	May Occur		Conditions to Avoid None known	
	Will Not Occur	X		
SECTION VI -Health Hazard Data				
Routes of Entry:		Inhalation? <div style="text-align: center;">Yes</div>	Skin? <div style="text-align: center;">Yes</div>	Ingestion? <div style="text-align: center;">Yes</div>
Health Hazards (<i>Acute and Chronic</i>)				
None.				
Carcinogenicity:		NTP? <div style="text-align: center;">No</div>	IARC Monographs <div style="text-align: center;">No</div>	OSHA Regulated? <div style="text-align: center;">No</div>
This product does not contain any ingredient designated by IARC, NTP, ACGIH, or OSHA, as probable or suspected human carcinogens				
Signs and Symptoms of Exposure				
Inhalation: No known signs or symptoms associated with exposure to product.				
Eye Contact: Slightly irritating. Does not injure eye tissue				
Ingestion: No known signs or symptoms associated with exposure to product.				
Skin Contact: Mild skin irritation is possible.				
Medical Conditions Generally Aggravated by Exposure				
N/A				
Emergency and First Aid Procedures				
Inhalation: Move exposed person to fresh air. If irritation persists, get medical attention promptly.				
Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation develops, consult a physician.				
Ingestion: Do not induce vomiting. If victim is conscious give plenty of water or milk to drink. Get medical attention immediately.				
Skin Contact: Flush contaminated skin with plenty of water. Consult a physician if irritation develops.				
SECTION VII -Precautions for Safe Handling and Use				
Steps To Be Taken in Case Material Is Released or Spilled				
Control spill with paper towel. Dried refuse may be disposed of according to local, state and federal regulations.				
Waste Disposal Method				
Dried refuse may be disposed of according to local, state and federal regulations. Check with local authorities for details on disposal.				
Precautions to Be Taken in Handling and Storing				
Store material in a cool, dry and well ventilated area between 40°F-90°F. Keep containers closed and air tight. Avoid freezing.				
Other Precautions				
Keep container tightly closed when not in use.				
KEEP OUT OF REACH OF CHILDREN.				

SOBO PREMIUM CRAFT FABRIC GLUE

SECTION VIII -Control Measures

Respiratory Protection (*Specify Type*)

Ventilation	Local Exhaust	Recommended	Special	None
	Mechanical (<i>General</i>)	May be used.	Other	None

Protective Gloves

Impervious plastic or rubber.

Protective Glasses

Safety glasses may be worn to avoid eye contact.

Other Protective Clothing or Equipment

Long sleeve garments may be worn to avoid contact with skin.

Work/Hygenic Practices

Clean-up with soap and water. Wash hands with soap and water after using product. Close container tightly.

SECTION IX - Disclaimer

Delta Creative, Inc. Assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the product. Such vendees assumes all risks associated with the use of this product.

THE INFORMATION GIVEN AND RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. ALL SUCH INFORMATION IS BELIEVED TO BE TRUE AND ACCURATE TO THE BEST OF OUR KNOWLEDGE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THE OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.

HMIS SYMBOL

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PROTECTION	0

RATING

SEVERE	4
SERIOUS	3
MODERATE	2
SLIGHT	1
MINIMAL	0

Transportation Information:

D.O.T. : Not Regulated
 I.A.T.A.: Not Regulated
 CERCLA RQ: None