MATERIAL SAFETY DATA SHEET

Page 1 of 8

MSDS-078

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 08/01/2008 PRODUCT IDENTIFICATION RAPIDRY SPRAY NAIL POLISH DRYER 1.2 Chemical Name DISILOXANE MIXTURE 1.3 Synonyms: NA 1.4 AL 702, AL 703, AL 704, AL 706, AL 707, AL 709 1.5 Product Use PROFESSIONAL OR SUNDRY USE ONLY 1.6 Manufacturer's Name OPI PRODUCTS, INC. 1.7 Manufacturer's Address 13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 +1 (818) 759-2400 / +1 (800) 341-9999 2. HAZARD IDENTIFICATION 2.1 This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC:1088 (2004) and ADG Code (Australia). Flammable liquid. 2.2 YES Inhalation: Absorption: Ingestion: 2.3 Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflammation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Odor may give some warning of exposure, but odor fatigue may occur. 24 Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. Acute Health Effects Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 2.6 Chronic Health Effects The material may accentuate any pre-existing dermatitis condition. None known 2.7 Target Organs Eyes, skin & respiratory system. NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.

MATERIAL SAFETY DATA SHEET

Page 2 of 8

MSDS-078

Prepared to OSHA ACC ANSL NOHSC WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

PROTECTIVE EQUIPMENT

SKIN

EYES

В

Prep	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards				MSDS Revision: 2.0 MSDS Revision Date: 08/01/2008										
			3 CC	MPOSITIO		PEDIEN	IT INI	E O D	MA A TI	ON					
3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³)															
							ACGIH		1	NOHSC			OSHA		
							ppm		ppm		ppm			OTHER	
	CHEMICAL NAME(S)		CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	
DISILOXANE		107-46-0	JM9237000	203-492-7	≤ 50.0	(0.3)	NE	NF	NF	NF	(0.3)	NE	NE		
C7-8	ISOPARAFFIN		70024-92-9	NA	274-273-1	≤ 50.0	NA	NA	NF	NF	NF	NA	NA	NA	
ETHYL	HEXYL PALMITA	ATE	29806-73-3	NA	249-862-1	≤ 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
FRAG	RANCE (PARFU	M)	NA	NA	NA	≤ 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
BENZ	YL BENZOATE		120-51-4	DG4200000	204-402-9	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
BENZ	YL SALICYLATE		118-58-1	VO1750000	204-262-9	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
BUTYL	PHENYL METHY	LPROPIONAL	80-54-6	MW4895000	201-289-8	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
CITRO	NELLOL		106-22-9	RH340000	203-375-0	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
GERA	NIOL		106-24-1	RG5830000	203-377-1	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
	L CINNAMAL		101-86-0	GD6560000	202-983-3	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
CYCL	HYDROXYISOHEXYL 3- CYCLOHEXENE CARBOXALDEHYDE		51414-25-6	NA	257-187-9	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
LINAL	.OOL		78-70-6	RG5775000	201-134-4	< 0.1	NE	NE	NF	NF	NF	NE	NE	NE	ALLERGEN
					FIDST AID	1	IDEC								
	First Aid:			4. 1	FIRST AID I	MEAS	JKE2								
4.1	INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove all contaminated clothing, including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately. INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.														
4.2	Medical Condition	-		W 1 P					HEA	LTH					1
	Pre-existing d skin, respirato	•	ner skin condi	tions, and disc	orders of the to	arget org	ans (e	yes,	FLAMMABILITY						3
									REACTIVITY				0		

$0.9 \cdot 1$

MATERIAL SAFETY DATA SHEET

Page 3 of 8

MSDS-078

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 08/01/2008 5. FIREFIGHTING MEASURES Flashpoint & Method: -7 °C (19 °F) 5.2 Autoignition Temperature: NA 5.3 Flammability Limits: 1.5 11.6 Lower Explosive Limit (LEL): Upper Explosive Limit (UEL): Fire & Explosion Hazards: This product is an extremely flammable liquid. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO₂, NO_x). Extinguish all nearby sources of ignition as vapors may travel and flash back. 5.5 Extinguishing Methods HazChem Code: 3YE Hazard Identification Number: 33 Water, Foam, CO₂, Dry Chemical Firefighting Procedures First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH-approved self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before returning to service. 6. ACCIDENTAL RELEASE MEASURES Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING & STORAGE INFORMATION

7.1 Work & Hygiene Practices

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap & water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink, or smoke while handling this product.

7.2 Storage & Handling

Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devices. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. Keep away from children at all times!

7.3 Special Precautions

Store in original container. Do not store where temperatures can exceed 120 °F.

MATERIAL SAFETY DATA SHEET

Page 4 of 8

MSDS-078

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 08/01/2008 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Ventilation & Engineering Controls: 8.1 Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station). 8.2 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.3 Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.4 None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., \geq 1 gallon), wear rubber or impervious plastic gloves. No apron required when handling small augntities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. 9. PHYSICAL & CHEMICAL PROPERTIES Density: 0.76 9.2 Boiling Point: 212 °F 9.3 Meltina Point: ND Evaporation Rate: 9.4 < 1.0 (n-BuAc = 1.0)95 Vapor Pressure ND 9.6 Molecular Weight: NE 9.7 Appearance & Color: Clear liquid with characteristic odor. 98 Odor Threshold Solubility: 9.9 Immiscible with water NΑ 9 11 Viscosity: < 500 cPs 9.12 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Relatively stable under ambient conditions when stored properly. 10.2 Hazardous Decomposition Products If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen). 10.3 Hazardous Polymerization Will not occur. 10.4 Conditions to Avoid: Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame. 10.5 Incompatible Substances Strong oxidizers, peroxides, acids, alkalis, combustible materials.

MATERIAL SAFETY DATA SHEET

Page 5 of 8

MSDS-078

Prep	pared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0 MSDS Revision Date: 08/01/2008
	11. TOXICOLOGICAL INFORMATION
11.1	Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity: See Section 2.5
11.3	Chronic Toxicity: See Section 2.6
11.4	Suspected Carcinogen: No
11.5	Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity: This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity: This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity: This product is not reported to cause reproductive effects in humans.
11.6	Irritancy of Product: See Section 2.3
11.7	Biological Exposure Indices: NE
11.8	Physician Recommendations: Treat symptomatically.
	12. ECOLOGICAL INFORMATION
12.1	Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are available, but are not presented in this MSDS.
12.2	Effects on Plants & Animals: There is no specific data available for this product.
12.3	Effects on Aquatic Life: There is no specific data available for this product. Releases of large volumes may be harmful or fatal to overexposed aquatic life. Aquatic toxicity data for components of this product are available, but are not presented in this MSDS.
	13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal: Dispose in accordance with local, state and Federal hazardous waste laws.
13.2	Special Considerations: U.S. EPA Characteristic Waste: D001 (ignitability)

MATERIAL SAFETY DATA SHEET

Page 6 of 8

MSDS-078

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CER IATA/ICAO IMDG and the CIDGR

Add	itional descriptive information may be required by 49 CFR, IATA/ICAO, INIDG and the CTDGR.
14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, II (> 1.0 L)
14.2	IATA (AIR):
	CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, II (> 0.5 L)
14.3	IMDG (OCN):
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, 11, LTD QTY (≤ 1.0 L)
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, II (> 1.0 L)
14.4	TDGR (Canadian GND):
	MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, II (> 1.0 L)
14.5	ADR/RID (EU):
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, 11, ADR, LTD QTY (≤ 1.0 L)
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, 11, ADR (> 1.0 L)
14.6	MEXICO (SCT):
	UN1993, LIQUIDOS INFLAMABLES, N.E.P. (hexametildisiloxano, isoparafina), 3, II
	CANTIDAD LIMITADA (≤ 1.0 L)
14.7	ADGR (AUS):
	UN1993, FLAMMABLE LIQUIDS, N.O.S. (hexamethyldisiloxane, isoparaffin), 3, II (> 1.0 L)



15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

15.2 SARA Threshold Planning Quantity:

15.3

All components of this product are listed in the TSCA Inventory or are exempt.

15.4 CERCLA Reportable Quantity (RQ):

15.5 Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics)

Other Canadian Regulations 15.6

> This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.



15.7 State Regulatory Information:


Eugenol can be found on the California Right to Know List.

No components of this product are listed on the California Proposition 65 lists.

15.8 67/548/EEC (European Union) Requirements:

The primary component of this product is listed in Annex I of EU Directive 67/548/EEC:

Hexamethyldisiloxane (CAS 107-46-0): Flammable (F). R: 11 - Highly flammable. S: 2-9-16-23-24-33-51 - Keep out of the reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Avoid contact with skin. Take precautionary measures against static discharges. Use only in well-ventilated areas.







Phone: +1 (310) 370-3600

e-mail: shipmate.com

Fax: +1 (310) 370-5700

MATERIAL SAFETY DATA SHEET

Page 7 of 8

MSDS-078

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

	16. OTHER INFORMATION					
16.1						
	Keep out of reach of children. Do not take internally. Store in a cool, dry place. Keep away from heat and open flame.					
16.2	2 Terms & Definitions:					
	Please see last page of this MSDS.					
16.3	3 Disclaimer:	•				
	This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relate to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. may be changed from time to time. Be sure to consult the latest edition.	e, the e not s only				
16.4	Prepared for: OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA +1 (818) 759-2400 phone +1 (818) 759-5770 fax http://www.opi.com/					
16.5						

Dangerous Goods

Training & Consulting

MATERIAL SAFETY DATA SHEET

Page 8 of 8

MSDS-078

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 08/01/2008

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDs. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists	
TLV	TLV Threshold Limit Value	
OSHA	OSHA U.S. Occupational Safety and Health Administration	
PEL	PEL Permissible Exposure Limit	
IDLH	Immediately Dangerous to Life and Health	

FIRST AID MEASURES:

				method in		
				receives		
compre	ssions a	nd bre	eathing to	circulate blo	od and	provide
OWIGOD	to the h	odv	_			


HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1 Slight Hazard	
2 Moderate Hazard	
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:







OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition	Minimum temperature required to initiate combustion
Temperature	in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by
	volume, that will explode or ignite in the presence of
	an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air,
	by volume, that will explode or ignite in the presence of
	an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-₩ -	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the
	exposed animals s
LC ₅₀	Lethal concentration (gases) which kills 50% of the
	exposed animal
ppm	Concentration expressed in parts of material per
	million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or
TC, TCo, LCIo, & LCo	toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					

EC INFORMATION:

		M	*		9	×	X
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful