# REDKEN

## SAFETY DATA SHEET

1. Identification

Product identifier REDKEN VOLUME MAXIMIZER THICKENING SPRAY

Other means of identification

**SDS number** 30-31-0000070

**Recommended use** Personal care product used for cosmetic effect.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

**US Address:** L'Oreal USA Products, Inc

133 Terminal Avenue Clark. NJ 07066

USA

Canadian Address: L'Oreal Canada

4895 rue Hickmore

Ville St-Laurent, H4T 1K5

Canada

**Emergency Phone #:** 1-800-535-5053 (International: 352-323-3500)

In Canada - 1-613-996-6666 (Canutec (\*666 Cellular))

For further Information: 1-732-499-2741

**Poison Control #:** 412-390-3326

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

In case of fire: Use appropriate media to extinguish.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: REDKEN VOLUME MAXIMIZER THICKENING SPRAY 35237RDK1 Version #: 03 Revision date: 01-12-2021 Issue date: 02-06-2020

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ETHANOL		64-17-5	5.7

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Not available.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an

ambulance. Continue flushing during transport to hospital.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves.

Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor. General fire hazards

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)					
Components	Туре	Value			
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3			
		1000 ppm			
US. ACGIH Threshold Limit Values					
Components	Туре	Value			
ETHANOL (CAS 64-17-5)	STEL	1000 ppm			
US. NIOSH: Pocket Guide to Chemical Hazards					
Components	Туре	Value			
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3			

Biological limit values
Appropriate engineering
controls

No biological exposure limits noted for the ingredient(s).

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

1000 ppm

Individual protection measures, such as personal protective equipment

**Eye/face protection** Applicable for industrial settings only. Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Applicable for industrial settings only. Wear appropriate chemical resistant gloves.

Other Applicable for industrial settings only. Wear appropriate chemical resistant clothing.

**Respiratory protection** Applicable for industrial settings only. If engineering controls do not maintain airborne

concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be

worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Gel.
Color Colorless.
Odor Characteristic.
Odor threshold Not available.
pH 7.2 - 7.8

Melting point/freezing point Not available.

Initial boiling point and boiling

> 212 °F (> 100 °C)

range

Flash point 136.4 °F (58.0 °C) Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

**Explosive properties** Not explosive.

Fire point > 212.00 °F (> 100.00 °C) ISO 2592

Oxidizing properties Not oxidizing.

10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

#### 11. Toxicological information

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

No adverse effects due to eye contact are expected.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

**Acute toxicity** 

Material name: REDKEN VOLUME MAXIMIZER THICKENING SPRAY 35237RDK1 Version #: 03 Revision date: 01-12-2021 Issue date: 02-06-2020

**Product Species Test Results** 

REDKEN VOLUME MAXIMIZER THICKENING SPRAY

Acute

Oral

**ATEmix** 252500 mg/kg Components **Species Test Results** 

ETHANOL (CAS 64-17-5)

**Acute Dermal** 

LD50 Rabbit > 20000 mg/kg

Inhalation

Vapor

LC50 Rat 124.7 mg/l, 4 h OECD 403

Oral

LD50 Rat 10470 mg/kg OECD 401

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. No adverse effects due to

skin contact are expected.

Irritation Corrosion - Skin

**ETHANOL OECD 404** 

> Result: Not Irritating Species: Rabbit

Serious eye damage/eye

irritation

Due to partial or complete lack of data the classification is not possible. No adverse effects due to

eye contact are expected.

Irritation Corrosion - Eve

**ETHANOL OECD 405** 

Result: Irritating Species: Rabbit

Respiratory or skin sensitization

Due to partial or complete lack of data the classification is not possible. Respiratory sensitization Skin sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization

**ETHANOL OECD 406** 

> Result: Not Sensitizing Species: Guinea pig

Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity

Mutagenicity

**ETHANOL** Result: In vitro and in vivo tests did not show mutagenic

effects.

Carcinogenicity Not classifiable as to carcinogenicity to humans. Due to partial or complete lack of data the

classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard.

**Developmental effects** 

**ETHANOL** > 20000 ppm OECD 414, No effects on development

Result: NOAEL Species: Rat

Reproductivity

**ETHANOL** 20700 mg/kg bw/d OECD 416, No effects on fertility

> Result: NOAEL Species: Rat

Specific target organ toxicity -Due to partial or complete lack of data the classification is not possible. single exposure

Material name: REDKEN VOLUME MAXIMIZER THICKENING SPRAY

Specific target organ toxicity repeated exposure

Due to partial or complete lack of data the classification is not possible.

1730 mg/kg bw/d OECD 408, Oral Result: NOAEL

Species: Rat

**Aspiration hazard** 

Due to partial or complete lack of data the classification is not possible.

**Further information** 

**ETHANOL** 

The reference to any animal testing for individual constituents mentioned in this document is

based on public, third-party data.

#### 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
ETHANOL (CAS 64-1	7-5)			
Aquatic				
Acute				
Algae	EC50	Pseudokirchneriella subcapitata	22200 mg/l, 96 h	
Crustacea	EC50	Ceriodaphnia dubia	5012 mg/l, 48 h	
Fish	LC50	Pimephales promelas	15300 mg/l, 96 h	
Other	IC50	Activated sludge of a predominantly domestic sewage	> 1000 mg/l, 3 h	
Chronic				
Crustacea	NOEC	Daphnia magna	9.6 mg/l, 9 d	
Fish	NOEC	Danio rerio	250 mg/l, 120 h OECD 212	

#### Persistence and degradability

Biodegradability

Percent degradation (Aerobic biodegradation)

**ETHANOL** 

Result: Readily Biodegradable

Test Duration: 20 d

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

**ETHANOL** -0.31

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions** 

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

This product is ignitable (D001) RCRA hazardous wastes when intended for disposal. Hazardous waste code

Waste from residues / unused Dispose of in accordance with local regulations. Empty containers or liners may retain some products

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

**FINISHED GOODS** 

Not regulated as dangerous goods.

**BULK** 

Not regulated as dangerous goods.

Material name: REDKEN VOLUME MAXIMIZER THICKENING SPRAY 35237RDK1 Version #: 03 Revision date: 01-12-2021 Issue date: 02-06-2020

#### IATA

#### **FINISHED GOODS**

Not regulated as dangerous goods.

**BULK** 

Not regulated as dangerous goods.

**IMDG** 

#### **FINISHED GOODS**

Not regulated as dangerous goods.

**BULK** 

Not regulated as dangerous goods.

In accordance with international transport regulations products associated with this document have **General information** 

been determined to have a flash point greater than 35°C and fire point greater than 100°C,

therefore these materials are exempt from flammable liquid transport regulations.

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

ETHANOL (CAS 64-17-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHANOL (CAS 64-17-5)

## 16. Other information, including date of preparation or last revision

Issue date 02-06-2020 01-12-2021 Revision date

Version # 03

NFPA ratings Health: 0

Flammability: 2 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: REDKEN VOLUME MAXIMIZER THICKENING SPRAY

Revision information	This document has undergone significant changes and should be reviewed in its entirety.